This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Canceled).
- 2. (Currently amended): A waveguide optical device comprising:
- a waveguide for guiding light wherein said waveguide comprises a ridge waveguide portion formed as a substantially stripe convex portion extending in a guiding direction, and a gain waveguide portion which guides light in a gain region optically coupled with said ridge waveguide portion; A device according to claim 1, further comprising:

an electrode formed on the an upper surface of said waveguide;

an extended portion extending from said gain waveguide portion in the a lateral direction of said waveguide; and

an electrode pad connected to said electrode and extending on the upper surface of said extended portion.

- 3. (Currently amended) A device according to claim 2, wherein the a resistance in at least a portion of said extended portion is increased to suppress injection of an electric current from said electrode pad.
- 4. (Currently amended) A device according to claim 3, wherein the <u>a</u> length of said gain waveguide portion is not more than 1/10 the <u>a</u> overall length of said waveguide.
- 5. (Original) A device according to claim 4, further comprising a diffraction grating formed along said waveguide to give optical perturbation to light to be guided,

Appl. No. 09/819,225 Amdt. Dated October 10, 2003 Reply to Office Action of July 11, 2003 Attorney Docket No. 81788.0191 Customer No. 26021

wherein said gain waveguide portion has a substantially phase shift effect on light guided in said waveguide.

- 6. (Original) A device according to claim 5, wherein said waveguide optical device is a distributed feedback laser which generates laser oscillation in said waveguide, and the phase shift effect of said gain waveguide portion changes in accordance with a bias current or threshold current supplied to said laser.
- 7. (Original) A device according to claim 6, wherein the change in the phase shift effect is so produced as to cancel chirping.
- 8. (Original) A device according to claim 2, wherein an insulating layer is formed between said electrode pad and at least a part of said extended portion, in order to suppress injection of an electric current from said electrode pad.
- 9. (Currently amended) A device according to claim 8, wherein the \underline{a} length of said gain waveguide portion is not more than 1/10 the \underline{a} overall length of said waveguide.
- 10. (Original) A device according to claim 9, further comprising a diffraction grating formed along said waveguide to give optical perturbation to light to be guided,

wherein said gain waveguide portion has a substantially phase shift effect on light guided in said waveguide.

11. (Original) A device according to claim 10, wherein said waveguide optical device is a distributed feedback laser which generates laser oscillation in said waveguide, and the phase shift effect of said gain waveguide portion changes in accordance with a bias current or threshold current supplied to said laser.

Appl. No. 09/819,225 Amdt. Dated October 10, 2003 Reply to Office Action of July 11, 2003

- 12. (Original) A device according to claim 11, wherein the change in the phase shift effect is so produced as to cancel chirping.
- 13. (Currently amended) A device according to claim 2, wherein the <u>a</u> length of said gain waveguide portion is not more than 1/10 the <u>a</u> overall length of said waveguide.
- 14. (Original) A device according to claim 2, further comprising a diffraction grating formed along said waveguide to give optical perturbation to light to be guided,

wherein said gain waveguide portion has a substantially phase shift effect on light guided in said waveguide.

15. (Currently amended) A waveguide optical device comprising:

a waveguide for guiding light wherein said waveguide comprises a ridge waveguide portion formed as a substantially stripe convex portion extending in a guiding direction, and a gain waveguide portion which guides light in a gain region optically coupled with said ridge waveguide portion, A device according to claim 1, wherein the a length of said gain waveguide portion is not more than 1/10 the an overall length of said waveguide.

16. (Original) A device according to claim 15, further comprising a diffraction grating formed along said waveguide to give optical perturbation to light to be guided,

wherein said gain waveguide portion has a substantially phase shift effect on light guided in said waveguide.

17. (Original) A device according to claim 16, wherein said waveguide optical device is a distributed feedback laser which generates laser oscillation in

Appl. No. 09/819,225 Amdt. Dated October 10, 2003 Reply to Office Action of July 11, 2003 Attorney Docket No. 81788.0191 Customer No. 26021

said waveguide, and the phase shift effect of said gain waveguide portion changes in accordance with a bias current or threshold current supplied to said laser.

18. (Original) A device according to claim 17, wherein the change in the phase shift effect is so produced as to cancel chirping.